



TECHNICAL DATA SHEET (TDS)

POLYESTER MESH CL12 84/167 P

N°	SF2014-24
Date of previous issue:	10/11/2015
Date of issue:	03/02/2016
Version:	2

Product type	Polyester Mesh
Denomination	CL12 84/167 P
Scrim weight	gr/mq. 12 +/- 1

Warp type yarn: polyester

Technical characteristics	unit	target	ISO standard
Title	dtex	84	ISO 1889
Number of yarn for dm	n°	75 +/- 0,2	optical
Tensile strength at break	daN/5cm	15,5 +/- 0,5	ISO 3341
Elongation at break	%	20 +/- 2	ISO2062:1997

Weft type yarn: polyester

Technical characteristics	unit	target	ISO standard
Title	dtex	167	ISO 1889
Number of yarn for dm	n°	25 +/- 0,2	optical
Tensile strength at break	daN/5cm	10 +/- 0,5	ISO 3341
Elongation at break	%	25 +/- 2,5	ISO2062:1997

	unit	target
Standard length	mtl	20,000 +/- 500
Standard width	mm	1400 +/-5mm
Outside diameter	mm	800 max
Inside core diameter	mm	3'



Via Rasica, 56 – 24040 Osio Sopra (Bg)

Tel. 035.504236 – Fax 035.506993

P.IVA / C.F.: 03866860160